

FLEXO WASH

FW 30 ANILOX

This anilox roll and sleeve cleaning solution is used for deep cleaning of anilox rolls and gravure cylinders in FW model systems for all solvent-, water- and UV-based inks.

FEATURES:

- Monoethanolamine (MEA)-free solution
- Deep-cleaning
- Cleans all ink types and coatings
- For use in automated cleaning systems
- Water-based chemical
- Aluminum safe – safer for anilox sleeves
- Manufactured in the U.S.

BENEFITS:

- Triethanolamine (TEA) is substituted for MEA – meets CT state requirements
- Eco-friendly cleaning solution
- Long tank life
- Solution is filtered and recirculates
- Nonflammable; no flash point
- Ease of use

USE INSTRUCTIONS: Mix FW 30 Anilox cleaner 50:50 with water. Set machine temperature to 120°F - 140°F.

RECOMMENDED FOR: Anilox roll and gravure cylinders in FW model units

VOC (LBS./GAL.): 0.30 (36 grams per liter)

HMIS RATING: Health 2, Flammability 0, Physical Hazard 0

FOAMING: Low at use conditions

DETERGENT GRADE: Standard

PACKAGING: 5-gallon kits, 55-gallon drums and 330-gallon totes



FLEXOWASH

LEADING CLEANING TECHNOLOGY

For product purchases:

- * Visit our online store at www.flexowashus.com,
- * Email us at orders@flexowashus.com,
- * Call us directly at 888-493-5396.

ABOUT FLEXO WASH LLC

Flexo Wash technology helps customers print better. Our products will extend the life of anilox rolls and sleeves, gravure cylinders, flexo plates, flexo plate sleeves, press parts and rotary screens, while decreasing the make-ready down time between job runs. Flexo Wash provides “Leading Cleaning Technology” and we are the only company in the world to offer cleaning systems for every need.

