

# FLEXO WASH

## FW 862 ANILOX PRE-MIXED

FW 862 Anilox Pre-mixed is for deep-cleaning anilox rolls and gravure cylinders in FW model systems for all solvent-, water- and UV-based inks.

### FEATURES:

- Anilox cleaner used for specialty coating and adhesives
- Non-SARA 313 option
- Deep-cleaning
- Cleans all ink types and coatings
- For use in automated cleaning systems
- Water-based chemical
- Aluminum safe — safer for anilox sleeves
- Manufactured in the U.S.

### BENEFITS:

- Long tank life
- Eco-friendly cleaning solution
- Solution is filtered and recirculates — no disposal required
- Non-flammable
- Ease of use

**USE INSTRUCTIONS:** Use FW 862 Anilox Pre-mixed full strength (the solution is already pre-mixed with water). Set machine temperature to 120°F - 140°F.

**RECOMMENDED FOR:** Anilox rolls and gravure cylinders in FW model units

**VOC (LBS./GAL.):** 0.33 (39 grams per liter)

**HMIS RATING:** Health 2, Flammability 0, Physical Hazard 0

**FOAMING:** Low at use conditions

**DETERGENT GRADE:** Standard

**PACKAGING:** 5-gallon kits, 55-gallon drums and 330-gallon totes



**FLEXOWASH**  
LEADING CLEANING TECHNOLOGY

### For product purchases:

- \* Visit our online store at [www.flexowashus.com](http://www.flexowashus.com),
- \* Email us at [orders@flexowashus.com](mailto:orders@flexowashus.com),
- \* Call us directly at 888-493-5396.

### ABOUT FLEXO WASH LLC

Flexo Wash technology helps customers print better. Our products will extend the life of anilox rolls and sleeves, gravure cylinders, flexo plates, flexo plate sleeves, press parts and rotary screens, while decreasing the make-ready down time between job runs. Flexo Wash provides "Leading Cleaning Technology" and we are the only company in the world to offer cleaning systems for every need.

